



03/06/2024



## SLC A1 Standard Low 2m

## S40100

## **Product description**

Low and narrow aluminum profile from SLC, with a wide range of applications. Recommended for indirect lighting due to low build height between LED strip and cover.

Low and narrow aluminum profile from SLC, with a wide range of applications. Recommended for indirect lighting due to low build height between LED strip and cover. For surface or recessed installation. Optional clear or opal cover with a smooth surface.

Slim and low aluminum profile

Recommended for indirect lighting due to short distance between LED-strip and cover

- Wide range of applications
- For surface or recessed installation

Optional clear or opal cover with a smooth surface Distance to cover: 6,8 mm

## **Technical data**

Length	2000 Millimetre
Height	8 Millimetre
Material thickness	1,4 Millimetre
Model	Singular profile
Hole width	0 Millimetre
Snap-off	No
Material	Aluminium
Colour	Anthracite
Brand	SLC
Produced by	The Light Group

Width	17 Millimetre
Slit width	12,3 Millimetre
Profile shape	U-profile
Type of perforation	None
With toothing	No
Suitable for circuit integrity	No
Surface protection	Anodised
Color	Aluminium
GTIN	7070938057691
HS Code	76042990



THE LIGHT GROUP GmbH Am Schafbrinke 62 | 30519 Hannover | Germany Tel.: +49 (0)511 - 807 486 10 | E-Mail: info@tlg.no THE LIGHT GROUP AS Sagmyra 2A, 4624 | Kristiansand S | Norway Tel.: +47 38 00 21 01 | E-Mail : post@tlg.no