



SLC LED CEILING S400 2140TED 2700K CRI80 IP54 OP

03/06/2024

SLC1066



Product description

Dimmable with TED (Trailing edge) dimmers. Recommended dimmer: SLC SmartOne (S24019). With opal shield for a comfortable lighting experience. Wall or ceiling mounting. Perfect for hallways, stairs, bathrooms, and wardrobes. Push connector with strain relief. Quick installation.

Dimmable with TED (Trailing edge) dimmers
Recommended dimmer: SLC SmartOne (S24019)
With opal shield for a comfortable lighting experience
Wall or ceiling mounting
Perfect for hallways, stairs, bathrooms, and wardrobes
Push connector with strain relief
Quick installation

Technical data

Suitable for suspended mounting	No
Suitable for built-in mounting	No
Lamp type	LED not exchangeable
Housing material	Plastic
Material cover	Plastic, opal
Voltage type	AC
Type of control gear	LED operating device current-controlled
Dimming phase cut-off	Yes
Dimming RF	No
Light sharing	Symmetric
Light outlet	Direct
Impact strength	IK08

Suitable for ceiling mounting	Yes
Suitable for surface mounting	Yes
With light source	Yes
Housing colour	White
Type of grid	Matt
Nominal voltage	220 - 240 Volt
With control gear	Yes
Dimming programmable	No
Light distributor	Diffuser lens/optic/panel
Beam angle	Open beam/diffuse
Degree of protection (IP)	IP54
Protection class	II





Rated ambient temperature according to IEC -20 - 50 Degrees celsius

Suitable for lamp power 25 - 25 Watt

Luminaire efficacy 86 Lumen/Watt

Colour of light White

Colour rendering index CRI 80-89

Width 400 Millimetre

Length 400 Millimetre

Type of wiring Suitable for through wiring

Connection type Push-in clamp

Beam angle fixed 120

Operating temperature (Ta) -10°C ~ +45°C

Brand SLC

Produced by The Light Group

Emergency power supply integrated Yes

Max. system power 25 Watt

Rated luminous flux according to IEC 62722- 2140 Lumen

Colour temperature 2700 - 2700 Kelvin

Power factor 0,9

Height/depth 66 Millimetre

Outer diameter 400 Millimetre


Number of poles 3

Power factor 0,9

Color White

Control type Trailing edge

GTIN 7070938061681



Flux 2386 lm
Maximum 341.83 cd/klm
Position C=60.00 G=1.00
Efficiency: 100.00%
Date: 29-07-2021
Double Symmetrical

