




Click 560 BK CCT

03/06/2024

SLC8500

Product description

SLC Click is a flexible linear system with revolutionary fast installation. Build linear, square or more creative lighting solutions for your office, meeting room, corridors or other public spaces. Microprismatic cover incl.

Technical data

Suitable for surface mounting	Yes
Suitable for suspended mounting	Yes
Adjustability	Not adjustable
Nominal voltage	220 - 240 Volt
Type of control gear	LED operating device current-controlled
Dimming DALI-2	Yes
Light sharing	Symmetric
Beam angle	Wide beam 41-80°
Energy efficiency class of the light source a	E
Rated life time L70/B50 at 25 °C	100000 Hour
Lumen maintenance at median useful life of	90 Percentage
Failure rate at median useful life of 35,000 h	1,5 Percentage
Degree of protection (IP)	IP20
Protection class	II
Suitable for lamp power	18 - 18 Watt

Suitable for wall mounting	Yes
Suitable for ceiling mounting	Yes
Voltage type	AC/DC
Nominal current	450 - 450 Milliampere
With control gear	Yes
Light distributor	Diffuser lens/optic/panel
Reflector colour	White
Light outlet	Direct
Total harmonic distortion	15
Lumen maintenance at median useful life of	92 Percentage
Lumen maintenance at median useful life of	85 Percentage
Failure rate at median useful life of 50,000 h	2,5 Percentage
Impact strength	IK06
Rated ambient temperature according to IEC	-20 - 40 Degrees celsius
Max. system power	18 Watt





Colour of light	White
Colour rendering index CRI	90-100
Power factor	0,9
Colour of light adjustable	Positions
Beam angle adjustable	No
Width	58 Millimetre
Length	560 Millimetre
Number of poles	5
Connection type	Other
Colour consistency (McAdam ellipse)	SDCM3
Power factor	0,9
Beam angle fixed	75
Color	Black
Control type	DALI2 DT6
GTIN	7070938074025

Colour temperature	3000 - 4000 Kelvin
Rated luminous flux according to IEC 62722-	2250 Lumen
Flickering value Pst LM	1
Luminous flux adjustable	No
Stroboscope effect value SVM	0,008
Height/depth	74 Millimetre
Type of wiring	Through wiring included
Conductor cross section	0,75 Square millimetre
Luminaire efficacy	125 Lumen/Watt
Unified Glare Ratio (UGR)	19
MAX. qty on 16A Circuit Breaker (Type C)	70
Glare (UGR)	UGR<19
Operating temperature (Ta)	-20°C ~ +45°C
Brand	SLC
Produced by	The Light Group

