



SLC DL04 SQUARE X2 R83X2 BL TED 3000K CRI90 IP54 36°

14/03/2023

SLC1247



Product description

The SLC DL04 Square X2 is a square, tiltable (25°) recessed luminaire in a double version. Experience pleasant light with low glare and a good colour rendering index.

The SLC DL04 Square X2 is a square, tiltable (25°) recessed luminaire in a double version. Experience pleasant light with low glare and a good colour rendering index.

Dimmable (TED) driver included
Recommended dimmer: SLC SmartOne (S24019)
UGR<22
CRI Ra> 90
Quick connection box with Loop-in / Loop-Out
16 mm Cable/Tube connection



Technical data

Suitable for built-in mounting	Yes
Adjustability	Swivelling
With light source	Yes
Surface protection	Powder coating
Material cover	Plastic, transparent
Nominal voltage	220 - 240 Volt
Type of control gear	LED operating device current-controlled
Dimming phase cut-off	Yes
Light distributor	Reflector
Reflector colour	Silver

Suitable for ceiling mounting	Yes
Lamp type	LED not exchangeable
Housing material	Aluminium
Housing colour	Black
Voltage type	AC/DC
Nominal current	440 - 440 Milliampere
With control gear	Yes
Reflector	High-gloss
Light sharing	Symmetric
Beam angle	Medium beam 21-40°





Light outlet	Direct
Degree of protection (IP)	IP54
Rated ambient temperature according to IEC	-20 - 45 Degrees celsius
Colour of light	White
Colour rendering index CRI	90-100
Colour of light adjustable	No
Beam angle adjustable	No
Height/depth	56,4 Millimetre
Built-in width	183,5 Millimetre
Built-in length	83 Millimetre
Type of wiring	Suitable for through wiring
Conductor cross section	0,35 Square millimetre
Connection type	Push-in clamp
Colour rendering index (CRI/Ra)	90
Tilt-able (°)	25
Cut-out hole (Ø: mm)	2x83
Dimmable	Yes
Dimming range	1-100%
GTIN	7070938065658

Energy efficiency class of the light source a	F
Protection class	II
Max. system power	20 Watt
Colour temperature	3000 - 3000 Kelvin
Rated luminous flux according to IEC 62722-	1210 Lumen
Luminous flux adjustable	Continuously variable
Width	190 Millimetre
Length	95 Millimetre
Built-in height/depth	56 Millimetre
Built-in diameter	166 - 166 Millimetre
Number of poles	2
Connectable conductor cross section	1,5 - 2,5 Square millimetre
Colour consistency (McAdam ellipse)	SDCM3
Beam angle (°)	36
Glare (UGR)	UGR<22
Dimming method	Trailing edge
Type of control signal	Amplitude modulation (AM)
Brand	SLC
Produced by	The Light Group



